

Features

2:1/4:1 Wide Input Range

One Sixteenth Brick

Operating Temperature Range: -45~105°C

Approved to UKCA, CE, RoHS & REACH

Safety Standards to IEC/EN 62368-1 & EN 50155

Efficiency up to 91%

Single output 3.3~24V DC



28STBxy-S-x-B50-IP Series

DC/DC PCB Mount Power Supply



Ideal Power's 28STBxy-S-x-B50-IP 50W Sixteenth Brick DC/DC Converters Series are certified to UKCA, CE, RoHS, REACH & EN 62368-1/IEC 62368-1/EN 50155 Standards and comply with Efficiency Regulations. These are primarily used in ITE, Audio & Video, Railway Industries, and customised solutions are available upon request.

Part Number Structure


28STB	-	018	033	-	S	-	P	-	B	50
Series Name		Input Voltage (VDC)	Output Voltage (VDC)		Pin out		Remote control option		Shape	Watt
Supreme series		012 : 9-18	033 : 3.3		S : Dosa		P : Positive logic		B : Base	50
Sixteenth		018 : 9-36	050 : 5				N : Negative logic		Plate	
Brick		024 : 18-36	120 : 12						F : No	
		036 : 18-75	150 : 15						Flange	
		048 : 36-75	240 : 24							

Models

Model	Input		Current (A) Full load	Output			Efficiency Typ.(%)
	Voltage (V) Range	Nominal		Voltage (V)	Current (A)	Power (W)	
28STB018033-S-□-□50-IP	9-36	18	3.16	3.3	15.1	50	88
28STB018050-S-□-□50-IP	9-36	18	3.09	5	10.0	50	90
28STB018120-S-□-□50-IP	9-36	18	3.12	12	4.2	50	89
28STB018240-S-□-□50-IP	9-36	18	3.12	24	2.1	50	89
28STB024033-S-□-□50-IP	18-36	24	2.34	3.3	15.1	50	89
28STB024050-S-□-□50-IP	18-36	24	2.29	5	10.0	50	91
28STB024120-S-□-□50-IP	18-36	24	2.31	12	4.2	50	90
28STB036033-S-□-□50-IP	18-75	36	1.58	3.3	15.1	50	88
28STB036050-S-□-□50-IP	18-75	36	1.54	5	10.0	50	90
28STB036120-S-□-□50-IP	18-75	36	1.56	12	4.2	50	89
28STB036240-S-□-□50-IP	18-75	36	1.56	24	2.1	50	89
28STB048033-S-□-□50-IP	36-75	48	1.17	3.3	15.1	50	89
28STB048050-S-□-□50-IP	36-75	48	1.14	5	10.0	50	91
28STB048120-S-□-□50-IP	36-75	48	1.16	12	4.2	50	90

Description

Ideal Power Supreme series - Quarter Brick converter is composed of Isolated, board-mountable, fixed switching frequency DC-DC converters that use synchronous rectification to achieve extremely high-power conversion efficiency. These DC-DC converter modules use advanced power processing, control, and packaging technologies to enhance the performance, flexibility, reliability, and cost effectiveness of mature power components. Each module is six-sided metal case enclosed to provide protection from the harsh environments seen in many industrial and transportation applications



Input Data

Parameter	Notes and Conditions	Min.	Typ.	Max.	Unit
Transient Input Voltage Ranges	28STB012 models (100ms Max) 28STB018 models (100ms Max) 28STB024 models (100ms Max) 28STB036 models (100ms Max) 28STB048 models (100ms Max)	--	--	50 50 50 80 80	VDC
Operating Input Voltage Ranges	28STB012 models 28STB018 models 28STB024 models 28STB036 models 28STB048 models	9 9 18 18 36	12 18 24 36 48	18 36 36 75 75	VDC
Under-Voltage Lockout Start-up Voltage	28STB012 models 28STB018 models 28STB024 models 28STB036 models 28STB048 models	--	8.5 8.5 17.5 17.5 35.5	9 9 18 18 36	VDC
Under-Voltage Lockout Shutdown Voltage	28STB012 models 28STB018 models 28STB024 models 28STB036 models 28STB048 models	7 7 16 16 32	8 8 17 17 34	--	VDC
Input filter	All models, Built-in PI filter				
Enable Function Input	Positive logic	ON OFF	Open or 8 ~ 20 Short or 0 ~ 1.2		VDC
	Negative logic	ON OFF	Short or 0 ~ 1.2 open Open or 8 ~ 20		VDC

Output Data

Parameter	Notes and Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy	VNOM 50% Load	--	--	±1.5	%
Line Regulation	Low Line to High Line	--	--	±0.3	%
Load Regulation	10% to 100% Load	--	--	±0.5	%
Ripple & Noise Voltage	Bandwidth 20MHz and with 1μF MLCC Output Capacitor	--	1.5	--	%Vpk-
Temperature Coefficient	--	--	--	+0.04	% / °C
Transient Recovery Time	25% load step change	--	800	--	μSec
Transient Peak Deviation	ΔIo/Δt=2.5A/us	--	+2	--	%Vo
Start-Up Time	When use Enable Function	--	20	--	mSec.
Trimming Output Protection	VNOM 10% Load	--	+10	--	%
Output power protection	VNOM 10% Load	--	120	--	%
Over Voltage Protection	VNOM	--	120	--	%

General Specifications & Environmental Data

Parameter	Notes and Conditions	Min.	Typ.	Max.	Unit
Switching frequency	VNOM 2:1 wide 4:1 wide	270 220	300 260	330 300	kHz
Storage temperature range	All models	-55	--	125	C
Operating case temperature	All models	-45	--	105	m
Over temperature protection	All models, Auto. Recovery	--	110	--	C
Isolation Voltage Input to Output Input to Output to case	All models, 1 Minute	2250	--	--	VDC
Isolation Resistance Input to Output	All models, 500VDC, At 70%RH	100	--	--	MΩ
Isolation Capacitance Input to Output	All models	--	1500	--	pF
Humidity (non-condensing)	All models	--	--	95	%
Calculated MTBF	BellCore-TR-332@ 50°C G.B	--	1.6	--	M HR
Thermal shock			MIL-STD-810F		
Vibration	Environmental Engineering Experimental Tests		MIL-STD-810F		
Drop			MIL-STD-810F		
Weight	Shape-B (Base Plate) Shape-F (No Flange Base Plate)	34 (1.23)	33 (1.2)		g (oz.)
Dimensions	Shape-B (Base Plate) Shape-F (No Flange Base Plate)	1.49" x 1.46" x 0.52" (37.8 x 37.2 x 13.2mm) 1.48" x 1.08" x 0.52" (37.5 x 27.4 x 13.2mm)			
Case Material	Six-Sided Continuous Shield - Aluminium				
Potting material	Silicone				

Standards Compliance




Parameter	Standard	Test conditions	Performance criteria
Environmental Compliance	Reach; RoHS	--	Pass
EMI	EN55022	--	Class A / Class B
ESD	EN61000-4-2	±4 kV Air Discharge ±4 kV Contact Discharge	Crit. A
Radiated Immunity	EN61000-4-3	Level 2, 3 V/m	Crit. A
Fast Transient	EN61000-4-4	±2 kV Applied	Crit. A
Surge	EN61000-4-5	±2 kV Applied	Crit. A
Conducted Immunity	EN61000-4-6	Level 2, 3 V rms	Crit. A

It is recommended to protect the input by fuses or other protection devices.

Modules could meet EN55032 Class A and Class B standard with external components.

The information and specifications contained in this data sheet are believed to be correct at time of publication. All specifications are subject to change without notice. No rights under any patent accompany the sale of any such products or information contained herein.

Conducted EMI


Shape – B (Base Plate)

Shape – F (No Flange Base Plate)


Pin#	Dosa
1	-Vin
2	Enable
3	+Vin
4	+Vout
5	+Sense
6	Adjust
7	-Sense
8	-Vout

Pin Pitch tolerance: ± 0.01 [0.25]
 Pin Dimensions: $.XX \pm 0.02$ [$.X \pm 0.5\text{mm}$]
 Pin Material: Copper Alloy
 Pin Plating: Gold
 Dimensions in inches [mm]
 Tolerances: $.XX \pm 0.02$ [$.X \pm 0.5\text{mm}$]
 $.XXX \pm 0.001$ [$.X \pm 0.025\text{mm}$]

Mechanical Drawings & Pin Assignment

Input terminal value (typ.) 28STB036050-S-P-B50-IP @Vin = 36VDC, Iout =10A



Characteristic curves

Testing conditions are at typical input, $T_a = +25^\circ\text{C}$, full load (horizontal mount) Unless otherwise indicated




Figure 1 : Efficiency at Minimum, Nominal and Maximum Input Voltages VS. Output Load.




Figure 2 : Efficiency VS. Input Voltages at 100% rated power




Figure 3 : Ambient Temperature VS. Output Power Derating Curves (Note: 20LFM = Free Air)




Figure 4 : Case Temperature VS. Output rated Power (Note: 20LFM = Free Air)




Figure 5 : CH1 = Vout, CH3 = Nominal Input Typical Start-up waveform at Full load.




Figure 6 : CH1 = Vout, CH3 = Enable Pin Typical Start-up waveform. Input voltage pre-applied




Figure 7 : Transient Response at Output step load (Vin: Typical, 50~75% of output current; $\Delta I_o/\Delta t = 1\text{A}/\mu\text{s}$)




Figure 8 : Output Voltage Ripple & Noise at full load. (Vin: Typical, With Output Capacitor to add 1uF MLCC)

Trimming Output Voltage - For Single Output Models

Only the single output converters have a trim function. That allows users to adjust the output voltage from +10% to -10%, please refer to the trim table that follow for details. Adjustments to the output voltage can be used with a simple fixed resistor as shown in Figures 1 and 2. A single fixed resistor can increase or decrease the output voltage depending on its connection.

Note:

- ※ Trim adjustments higher than the specified range can have an adverse effect on the converter's performance and are not recommended.
- ※ If the trim function is not used, leave the trim pin open.




Figure 1. Trim Connections To increase Output Voltages Using Fixed Resistors




Figure 2. Trim Connections To Decrease Output Voltages Using Fixed Resistors

Trim up resistor value(KΩ)										
Vout	1%	2%	3%	4%	5%	6%	7%	8%	9%	10%
3.3	72.9	33.1	19.8	13.1	9.1	6.5	4.6	3.2	2.1	1.2
5	113.1	52.0	31.6	21.5	15.3	11.3	8.4	6.2	4.5	3.1
12	267.2	121.6	73.1	48.8	34.2	24.5	17.6	12.4	8.4	5.1
15	340.4	156.2	94.8	64.1	45.7	33.4	24.6	18.0	12.9	8.8
24	527.7	240.3	144.6	96.7	67.9	48.8	35.1	24.8	16.9	10.5

Enable Control Function

The primary-side, Enable Control function can be specified to operate with either positive or negative polarity. Positive-polarity devices are enabled when the enable pin is left open or is pulled high. See "Enable Function Input. Positive-polarity devices are disabled when the enable pin is pulled low (under +1.0V with respect to -input). Negative-polarity devices are off when the enable pin is high/open and on when the enable pin is pulled low. See Figure 3.




Figure 3. Driving the Enable Control pin

Trim down resistor value(KΩ)										
Vout	-1%	-2%	-3%	-4%	-5%	-6%	-7%	-8%	-9%	-10%
3.3	81.9	36.7	21.6	14.1	9.6	6.6	4.4	2.8	1.5	0.5
5	115.2	51.8	30.7	20.1	13.8	9.5	6.5	4.3	2.5	1.1
12	297.6	133.7	79.1	51.8	35.4	24.4	16.6	10.8	6.2	2.6
15	346.1	155.3	91.7	59.9	40.8	28.1	19.0	12.2	6.9	2.7
24	665.3	302.7	181.8	121.3	85.1	60.9	43.6	30.7	20.6	12.5

Output Ripple Noise

The two copper strips simulate real-world PCB impedances between the converter and its load. Scope measurements should be made using BNC connectors or the probe ground should be less than 1/2 inch and soldered directly to the fixture. All external capacitors should have appropriate voltage ratings and be located as close to the converter as possible. Temperature variations for all relevant parameters should be taken into consideration. The most effective combination of external I/O capacitors will be a function of line voltage and source impedance, as well as load and layout conditions. See Figure 4




Figure 4. Measuring Output Ripple/Noise(20MHz bandwidth)

